

Description

High-performance hydraulic oil made from high-quality raffinates. Because of the high thermal stability of the base oils, the aging process is significantly reduced even at elevated temperatures. This decisively helps to reduce the formation of sludge, improve cleanliness, and promote the reliability of the hydraulic systems. Excellent oxidation resistance permits extended oil change intervals. The outstanding wear-protection technology is effective in both, low and high load conditions. Maintains good corrosion protection behavior even if water is present. The hydraulic components are thus optimally protected in all operating conditions.

Properties

- high lubrication reliability
- outstanding corrosion protection
- outstanding thermal stability
- high resistance to aging
- does not attack common sealing materials
- excellent wear resistance

Approvals

Hydrauliköl DIN 51524 Teil 2 HLP 68

Technical data

ISO viscosity class	VG 68 DIN 51519
Density at 15 °C	0,885 g/cm ³ DIN 51757
Viscosity at 40 °C	68 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8,6 mm ² /s ASTM D 7042-04
Viscosity index	97 DIN ISO 2909
Pour point	-27 °C DIN ISO 3016
Flash point	240 °C DIN ISO 2592
Demulgation characteristics at 54 °C	<= 30 min DIN ISO 6614
Foaming behavior at 24 °C	30/0 ml ISO 6247
Foaming behavior at 93.5 °C	50/0 ml ISO 6247
Foaming behavior at 24 °C after 93.5 °C	30/0 ml ISO 6247
Air separation capacity	<= 13 min DIN ISO 9120



Technical data

Corrosion effect on steel	0-B DIN ISO 7120
Corrosion effect on copper	1-125 A3 DIN EN ISO 2160
Neutralization number	0,5 mg KOH/g DIN 51558 T1
Neutralization number after 1000 h	< 2 mg KOH/g DIN 51587
Oxide ash	0,16 g/100g DIN EN ISO 6245
Sulfate ash	0,17 g/100g DIN 51575
FZG gear rig test, standard test A/8, 3/90	Schadenskraftstufe >10, Spez.Gew.Änderung <0,27 mg/KWh DIN 51354
Color number (ASTM)	L 1,5 DIN ISO 2049

Areas of application

For stationary and mobile applications in hydraulic systems in construction, forestry and agricultural machinery such as excavators, tractors etc., hoists, industrial machinery and machine tools, wood splitters, lifting platforms and presses, etc. Due to its good compatibility with materials, this LIQUI MOLY hydraulic oil can be used in the most common pump systems in hydraulic units. This hydraulic oil can also be used with all mineral-oil-compatible sealing materials and coatings.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

20 l Canister plastic	1113 D-GB
60 l Drum sheet metal	1114 D-GB

Product information

PI 29/12/01/2021



Hydraulic Oil HLP 68

Available pack sizes

205 l Drum sheet metal 1115
D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.