# **Product information**

# Touring High Tech SAE 20W-50



# **Description**

Mineral based all-season motor oil, particularly suited for older generation high mileage gasoline and diesel vehicles. Provides a stable lubricating film even under extreme operating conditions. Designed with proven wear protection technology. Keeps rubber seals such as valve stem seals, crank seals, cam seals etc. soft and pliable for low oil consumption.

# **Properties**

- very good dispersion properties
- ideal with catalytic converters
- can be used in gasoline and diesel engines with and without turbocharger
- high lubrication reliability
- prevents black sludge
- low evaporation loss
- excellent wear resistance
- excellent cleaning effect
- optimum stability to aging
- high shear stability

## **Specifications / Approvals**

ACEA A3/B4. E2 • API SL • API CG-4 • Allison C4 • MIL-L 2104 E

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Caterpillar TO-2 • MAN 271 • MB 228.3

#### Technical data

20W-50 SAE class (engine oils) **SAE J300** 

0,880 g/cm<sup>3</sup>

Density at 59 °F DIN 51757

Viscosity at 104 °F  $165.0 \, \text{mm}^2/\text{s}$ 

ASTM D 7042-04

Viscosity at 212°F 18.5 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -4 °F (MRV) < 60000 mPas

ASTM D4684

Viscosity at 5 °F (CCS) < 9500 mPas

ASTM D5293

Viscosity index

**DIN ISO 2909** 

HTHS at 302 °F ≥ 3.7 mPas

ASTM D5481

-22 °F Pour point

**DIN ISO 3016** 



#### Technical data

Evaporation loss (Noack) 7.2 %

CEC-L-40-A-93

446 °F Flash point

**DIN ISO 2592** 

Total base number 10,2 mg KOH/g

PI 52/04/25/2023

**DIN ISO 3771** 

Sulfate ash 1,0 - 1,6 g/100g

DIN 51575

Color number (ASTM) L5.5

**DIN ISO 2049** 

# Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

#### **Application**

Observe the manufacturers instructions!

#### Available pack sizes

5 l Canister plastic 20114

USA-AND-CANADA-FN-F

22127 205 l Black plate barrel

USA-AND-CANADA-EN-F

1.000 l Container 22169

USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de