

Truck Gear Oil (GL4) 75W-90

Description

Fully synthetic gear oil ensures an outstanding function of the units even under high temperature fluctuations. Wear is reduced to a minimum. Ensures an excellent efficiency of the transmission and maximum fuel savings. Suitable for the maximum oil change intervals.

Properties

- secures optimum transmission operation
- excellent wear protection
- highest fuel economy
- extremely long oil change intervals

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

API GL4 • MB 235.11

Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,870 g/cm ³ DIN 51757
Viscosity at 40 °C	106,0 mm ² /s ASTM D7042
Viscosity at 100 °C	15,6 mm ² /s ASTM D7042
Viscosity index	157 DIN ISO 2909
Viscosity at -40 °C (Brookfield)	<150000 mPas ASTM D2983
Pour point	-51 °C DIN ISO 3016
Flash point	200 °C DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Areas of application

High performance gear oil for extended oil change intervals in commercial vehicle manual transmissions, especially for the Actros model series from Mercedes-Benz.

Application

Note the vehicle and unit manufacturer's instructions.

Available pack sizes



Available pack sizes

20 l Canister plastic	1446 D-GB
60 l Black plate barrel	1448 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.