Product information

PI 28/03/01/2023

legally binding.

Motorbike Fork Oil SAE 10W medium



Description

Full synthetic, medium-viscosity fork or shockabsorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

LIQUI MOLY FORK OIL 10W

Properties

- prevents seals from swelling
- prevents foam formation
- good corrosion protection
- high wear resistance
- better drivability

Technical data

Density at 59 °F 0,83 g/cm³

ASTM D 7042-04

Viscosity at 104 °F 28,5 mm²/s

DIN 51757

Viscosity at 212°F 5,7 mm²/s

ASTM D 7042-04

Viscosity index 146

DIN ISO 2909

Pour point -43 °F

DIN ISO 3016

Flash point 471 °F

DIN ISO 2592

Color number (ASTM) L 0,5

DIN ISO 2049

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes and other powersport vehicles where an oil with current product specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

Available pack sizes

1 l Can plastic 20092

USA-AND-CANADA-EN-F

20 l Canister plastic 20404

USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com