

Motorbike Gear Oil SAE 75W-90**Description**

Fully Synthetic, GL5 high-performance extreme-pressure gear oil. Facilitates smooth and precise shifting even in extreme conditions, provides excellent wear protection properties and ideal viscosity-temperature behavior.

**Properties**

- high efficiency
- excellent wear protection
- wide viscosity range
- reduces transmission noise
- good corrosion protection
- guarantees smooth gearshifting
- guarantees low fuel consumption

effectiveness only when the product is used undiluted.

Available pack sizes

1 l Can plastic 20086
USA-AND-CANADA-EN-F

Specifications / Approvals

API GL5 • MIL-L 2105 C • MIL-L 2105 D

Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 59 °F	0,855 g/cm ³ DIN 51757
Viscosity at 104 °F	80 mm ² /s ASTM D 7042-04
Viscosity at 212°F	14,3 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	185 DIN ISO 2909
Pour point	-70 °F DIN ISO 3016
Flash point	374 °F DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

Areas of application

Universal use in motorbike transmissions and final drives where a gear oil according to current product specifications is required or recommended.

Comment

⚠ WARNING: Cancer- www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions! Optimum

Our information is based on thorough research and may be considered reliable, although not legally binding.