

Motorbike Fork Oil 15W heavy

Description

Fully synthetic fork and shock absorber oil. Designed for universal use. Special synthetic base oils and corresponding additives guarantee optimum drivability and damping. Prevents the formation of foam and the hardening of seals. Good corrosion and wear protection ensures a long service life.

Properties

- high wear resistance
- prevents foam formation
- prevents seals from swelling
- lasting corrosion protection
- increases driving safety

Technical data

Density at 15 °C	0,835 g/cm ³ DIN 51757
Viscosity at 40 °C	45 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8 mm ² /s ASTM D 7042-04
Viscosity index	151 DIN ISO 2909
Pour point	-36 °C DIN ISO 3016
Flash point	260 °C DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, motor-assisted bicycles and other two-wheelers.

Application

Follow the instructions of the telescopic fork, shock absorber and two-wheel vehicle manufacturers.

Available pack sizes

500 ml Can plastic	1524 DE-EN-ES-IT-PT
500 ml Can plastic	5954 DE-FR-IT-NL
1 l Can plastic	2717 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

