Product information

Snowmobile Motor Oil 2T Pro Race



Description

Fully synthetic high-performance 2-stroke motor oil developed and tested on racing machines. Ensures maximum performance and protection of the engine in all operating conditions. Outstanding lubrication and engine cleanliness, excellent friction and minimum wear as well as less smoke. This oil improves the riding experience!

Properties

- reduces smoke formation and lowers emissions
- high wear resistance
- good corrosion protection
- residue-free combustion
- self mixing
- high thermal stability

Specifications and approvals

API TC • ISO L-EGD • JASO FD

Technical data

Density at 59 °F 0,875 g/cm³

DIN 51757

Viscosity at 104 °F 50 mm²/s

ASTM D 7042-04

Viscosity at 212°F 9,1 mm²/s

ASTM D 7042-04

Viscosity index 165

DIN ISO 2909

Pour point -48 °F

DIN ISO 3016

Flash point 98 °F

DIN ISO 2592

Total base number 2,3 mg KOH/g

DIN ISO 3771

Sulfate ash 0,15 g/100g

DIN 51575

Color/appearance red

Areas of application

Particularly for air or water cooled 2-stroke engines in Snowmobiles when a motor oil according to current product specifications is required or recommended. Self-mixing. A Pre-mix ratio up to 1:100 makes it perfectly suitable for E-Tec engines.

Comment

#P65 WARNING: Cancer- www.P65Warnings.ca.gov



Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

PI 12/10/05/2021

Available pack sizes

1 l Canister plastic 20144

USA-AND-CANADA-EN-F

4 l Canister plastic 20146

USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.