

Classic Transmission Oil SAE 90

Description

Mineral-based transmission oil specially for classic vehicles. Provides a stable lubricating film and minimizes wear. Provides good lubrication properties and ideal corrosion protection. Enables smooth shifting.

Properties

- minimizes wear
- reduces running noise
- good corrosion protection
- does not attack common sealing materials
- also suitable for classic motorcycles

and may be considered reliable, although not legally binding.



LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

API GL1 • API GL2 • API GL3 • Alfa Romeo • AMC •
BMW • Jeep • Opel • Rolls-Royce • Volkswagen •
Volvo

Technical data

SAE class (gear oils)	90 SAE J306
Density at 59 °F	0,88 g/cm ³ DIN 51757
Viscosity at 104 °F	181 mm ² /s ASTM D 7042-04
Viscosity at 212°F	16,5 mm ² /s ASTM D 7042-04
Viscosity index	95 DIN ISO 2909
Pour point	-11 °F DIN ISO 3016
Flash point	453 °F DIN ISO 2592
Color number (ASTM)	L 3,5 DIN ISO 2049

Areas of application

For manual transmissions under low load in classic vehicles, where an API GL1/GL2/GL3-compliant gear oil is required.

Application

When selecting the product, choose the viscosity class stipulated by the transmission manufacturer. Mixable with all branded gear oils. Full effectiveness only achieved when the product is used on its own (i.e. no mixing).

Our information is based on thorough research