Product information

PI 22/06/27/2022

Chain lubrication oil for forklift trucks



Description

High-quality, thermostable, adherent and synthetic lubricant compound. With selected white solid lubricants that provide additional lubrication properties and show where the product has been applied. Suitable for all types of chains. Reduces chain elongation thanks to high pressure absorption capacity.



Our information is based on thorough research and may be considered reliable, although not - excellent creep properties legally binding.

Properties

- especially cold, hot and splash-water resistant
- high pressure-absorption capability
- optimum effectiveness when the product is used unmixed
- reduces chain elongation
- reduces friction and prevents stick slip
- outstanding corrosion protection
- excellent adhesion

Technical data

Color / appearance colourless, clear Base oil with adhesion

improver

Operating temperature

range

-30 to +180 , shortperiods up to 200 °C

Water resistance at 90 °C

DIN 51 807

Form aerosol, liquid Odor characteristic 60 months Shelf life in original

sealed container

Areas of application

For initial and maintenance lubrication of powertransmission chains. Especially suitable for dusty, dirty and corrosive environments. Ideal for high-load chains thanks to extremely good adherence.

Application

Carefully clean chain with solvent. Then spray with the chain lubrication oil. The lubricant attains its final consistency and adherence once the solvent has evaporated.

Available pack sizes

400 ml Can aerosol 20946

D-GB-I-E-P

400 ml Can aerosol 2282

D-RUS-UA

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de