

PTFE Longlife Spray

Description

Synthetic high-performance lubricant with PTFE. The high pressure and temperature resistances as well as the excellent water resistance help to ensure a lasting lubricant film. The solid lubricant ensures very good damping and emergency running characteristics. Extremely adherent and penetrative.

Properties

- universal application
- excellent adhesion
- outstanding corrosion protection
- wide operating temperature range
- suppresses noise and vibration
- good water resistance
- has a lasting effect
- highest load-carrying capacity

Technical data

Color / appearance	yellow
Form	aerosol, liquid
Odor	characteristic
Operating temperature range	-30°C bis +180°C, kurzzeitig bis +200°C

Areas of application

For preventive periodic lubrication of components in the automotive, commercial vehicle, construction machinery and industrial sector and for eliminating popping and creaking on hinges, joints, linkages, relay levers, spindles, guides, slide rails, door retaining straps, door bolts, etc. Also suitable as a release agent if used sparingly.

Comment

The specifications and instructions from the assembly or vehicle manufacturer must be followed.

Application

Spray onto the cleaned parts that are to be treated. Even greater penetrative effectiveness can be obtained by reducing the spraying distance.

Available pack sizes

400 ml Can aerosol 20971
D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.

