

Pro-Line JetClean Diesel Intake System Cleaner

Description

Highly effective additive combination for direct use with the JetClean Tronic II. Removes typical contamination and deposits in the intake and throttle valve area. Loosens and removes dry and greasy contamination such as soot, oil, etc. Ensures the operability of all moving parts and reduces fuel consumption. Increases the reliability of diesel-powered engines.

Properties

- excellent cleaning effect
- cleaning possible without dismantling
- optimizes economical use
- rapid cleaning
- ready for use
- suitable for diesel particulate filters
- tested for turbocharger
- simple to use

Technical data

Form	liquid
Viscosity at 40 °C	<7 mm ² /s
Odor	characteristic
Density at 15 °C	0,894 g/cm ³
Flash point	-18 °C
Color / appearance	light yellow

Areas of application

For the intake and throttle valve area. Only for use in diesel engines!

Comment

Ready for use for undiluted filling of the JetClean Tronic II. A detailed description of further application is given in the instructions of the JetClean Tronic II.

Application

Ready for use for undiluted filling of the JetClean Tronic II. A detailed description of further application is given in the instructions of the JetClean Tronic II.

Available pack sizes

300 ml Can sheet metal 21274
GB-DK-FIN-N-S



Available pack sizes

300 ml Can sheet metal 20986
D-GB-E

Our information is based on thorough research and may be considered reliable, although not legally binding.