Description

Eliminates starting problems and noisy engine running. Ensures optimum spray diffusion. Removes deposits on the injection nozzle, intake valve, and spark plug, and in the combustion chamber. Prevents new deposits forming. Cares for all parts of the gasoline injection system and protects the entire fuel system against corrosion. Optimizes emissions values and engine performance. Clean engines consume less fuel and emit fewer pollutants.

Properties

- cleans the mixture preparation system as well as the intake valves and the combustion chamber
- prevents corrosion in the fuel system
- improves performance
- normalizes gasoline consumption and exhaust emissions

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light yellow, clear
Regulation on Flammable Liquids Class (Germany)	AII
Flash point	> 61 °C
Pour point	-45 °C
Form	liquid
Odor	characteristic
Viscosity at 40 °C	<7 mm²/s
Density at 15 °C	0,7989 g/ml

Areas of application

Suitable for all gasoline engines.

Application

Can is sufficient to treat up to 115 l of fuel. For optimum performance a minimum fill of 25 l is required. Add every 2,000 km before filling up.

Available pack sizes

500 ml Can sheet metal	20995 GB-F-RUS-ARAB
500 ml Can sheet metal	21454 GB-P

Our information is based on thorough research and may be considered reliable, although not legally binding.



