

Anti-bacterial Diesel additive

Description

Highly effective biocide with broad spectrum of activity against bacteria, yeast and mold. **Use biocides safely. Always read the label and product information before use.**

Properties

- prevents bacterial, yeast, and mold growth in tank systems
- preserves contaminated tank systems
- keeps injection nozzles clean
- improves the lubrication properties
- prevents expensive repairs

Technical data

Base	biocide, detergent and cetan number enhancer
Color / appearance	brown, clear
Density at 15 °C	0,8991 g/cm ³
Kinematic viscosity at 40°C	<7 mm ² /s
Flash point	< 63 °C
Regulation on Flammable Liquids Class (Germany)	A III
Shelf life in original sealed container	5 years
Odor	characteristic
Form	liquid

Areas of application

For preventive use in diesel-powered vehicles which are decommissioned for long periods or are infrequently used such as construction machinery, commercial vehicles, RVs, passenger cars or in storage tanks or for disinfection of contaminated tank systems. Not suitable for use with HVO diesel fuel.

Application

Dosage 1:1000. 25 ml sufficient for 25 l of diesel fuel. For preventative use, add the corresponding amount before filling the tank. With serious bacterial and fungal infestation with filter clogging, use a booster dose (dosage 1:200).

Available pack sizes

125 ml Can sheet metal	20940 EL-IT
1 l Can sheet metal	2368 DA-EN-FI-NO-SV
1 l Can sheet metal	21317 DE-EL-FR-IT

Available pack sizes

5 l Canister plastic	21318 DE-EN-ES
60 l Black plate barrel	21319 DE-EN-ES-FR-IT-PT



Our information is based on thorough research and may be considered reliable, although not legally binding.