

Tire Fitting Paste black

Description

Waxy fitting aid which contains special soap components and is formulated to aid the economic and efficient fitting of tires.

Properties

- keeps the tire bead supple
- counteracts rust formation
- prevents the tire from sticking to the rim
- facilitates fitting/removal
- quick drying
- no visible residues on tire edges
- high capacity
- simple to use
- good gliding properties
- absolutely skin tolerant
- suitable for run-flat tires
- suitable for tire pressure monitoring system TPMS
- can be used in the newest tire generations
- does not dry out after opening, even with extended storage
- biologically degradable
- silicone-free
- free of volatile organic compounds
- AOX-free

Technical data

Base	DEG, soap
Color / appearance	black
Density	~ 1 g/cm ³
pH value	~ 8
Form	creamy, solid
Flash point	~ 240 °C
Solubility in water	soluble
Odor	weak, odourless
Processing temperature	-10 bis +50
Shelf life	60 Monate

Areas of application

For fitting all standard wheel/tire combinations. Especially suitable for run-flat tires.

Application

Apply thinly and evenly with a brush or sponge onto the tire bead. On truck and EM tires, also paint the rim base and bead seat ring. This helps the tire to slide easily onto the rim without damage. Ensures the correct technical seat of the tire on the rim, which is a requirement for precise balancing and makes it easier to remove the tire later. Note the tire manufacturer's



instructions.

Available pack sizes

5 kg Bucket plastic 21345
D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.