

Top Tec ATF 1950

Description

Fully synthetic, low viscosity automatic transmission fluid, developed to fulfill strict requirements for Mercedes-Benz 9-speed automatic transmissions (type 725.0/1). Improved formula for sustained transmission life, maximum efficiency and best transmission shift performance.



Properties

- reduces fuel consumption
- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

Available pack sizes

1 l Can plastic	22034
	USA-AND-CANADA-EN-F
20 l Canister plastic	21379
	BOOKLET

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

MB 236.17

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Density at 59 °F	0,84 g/cm ³ DIN 51757
Viscosity at 104 °F	24 mm ² /s ASTM D 7042-04
Viscosity at 212°F	5,3 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 15000 mPas ASTM D 2983-09
Viscosity index	165 DIN ISO 2909
Pour point	-65 °F DIN ISO 3016
Flash point	356 °F DIN ISO 2592
Color / appearance	braun

Areas of application

For Mercedes-Benz 9-speed automatic transmissions where an ATF fluid meeting current product specification is required or recommended.

Application

Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.

Available pack sizes