## **Product information**

# Special Tec B FE SAE 5W-30



#### **Description**

Modern fully synthetic motor oil for superior performance and long engine life. Developed specifically for use in numerous BMW gasoline vehicles without particulate filter (GPF) from 2002 and later. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

### **Properties**

- outstanding engine cleanliness
- excellent resistance to aging
- minimizes friction
- ensures maximum engine performance
- saves fuel and reduces pollutant emissions
- ideal with turbochargers and catalytic converters

#### **Specifications / Approvals**

ACEA A5 • ACEA B5 • API SL

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW Longlife-01 FE

#### **Technical data**

Density at 59 °F

SAE class (engine oils) 5W-30 SAE J300

0.860 a/cm³

DIN 51757

DIN 51/5/

Viscosity at 104 °F 63,0 mm<sup>2</sup>/s

ASTM D7042

Viscosity at 212°F 10,6 mm²/s

**ASTM D7042** 

Viscosity at -31 °F (MRV) < 60000 mPas

ASTM D4684

Viscosity at -22 °F (CCS) <= 6600 mPas

**ASTM D5293** 

Viscosity index 160

**DIN ISO 2909** 

HTHS at 302 °F >= 3,0 mPas

ASTM D5481

Flash point 435 °F

DIN ISO 2592

Pour point -43 °F

**DIN ISO 3016** 

Evaporation loss (Noack) 9,7 %

CEC-L-40-A-93

Total base number 11,7 mg KOH/g

DIN ISO 3771



#### **Technical data**

Sulfate ash 1,4 g/100g

DIN 51575

Color number (ASTM) L 3,0

**DIN ISO 2049** 

#### Areas of application

For BMW gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

PI 16/11/21/2023

#### **Application**

Observe the manufacturers instructions!

#### Available pack sizes

1 l Canister plastic 20442

USA-AND-CANADA-EN-F

5 l Canister plastic 20444

USA-AND-CANADA-EN-F

20 l Canister plastic 22134

USA-AND-CANADA-EN-F

205 l Black plate barrel 22135

USA-AND-CANADA-EN-F

1.000 l Container 22165

USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com