Product information

PI 30/11/03/2026

Speed Tec Diesel



Description

Diesel fuel additive for improved combustion and consequently faster acceleration, particularly under partial load. Perfectly compatible with all conventional diesel and biodiesel fuels. Significantly improves vehicle acceleration.

Properties

- higher performance gain
- improves acceleration
- tested for the use with catalytic converters
- better drivability
- cleans the injection system
- suitable for diesel particulate filters
- does not influence the cetane number
- contains no organometallic compounds
- reduces frictional losses

Technical data

Base	Additive combination
Color / appearance	yellow, clear
Flash point	>63 °C
Form	flüssig, liquid
Viscosity at 40 °C	<7 mm²/s
Odor	characteristic
Density at 15 °C	0,822 g/cm³

Areas of application

Added to the diesel fuel. Especially suitable for diesel engines and fast vans. For the improvement of vehicle acceleration and smooth operation.

Application

One 250 ml can is sufficient for max. 70 liters of diesel fuel. Mix the contents of the can with the diesel fuel. Mixing also takes place automatically.

Available pack sizes

250 ml Can sheet metal	2367 DA-FI-NO-SV
250 ml Can sheet metal	3722 DE-EN-IT
250 ml Can sheet metal	21645 DE-ES-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com