

Marine 4T Motor Oil SAE 25W-50

Description

Heavy-duty motor oil formulated with specific synthetic marine additives. Provides a stable lubricating film and best wear protection in the most extreme conditions. Maintains engine rubber seals for lowest possible oil consumption.



Properties

- outstanding corrosion protection
- outstanding oil film strength
- stable to ageing and stable viscosity
- optimum oil pressure under all operating conditions
- ideal with turbochargers and catalytic converters

Specifications / Approvals

API SM • NMMA FC-W Catalyst Compatible®

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Mercury Marine • NMMA FC-W

Technical data

SAE class (engine oils)	25W-50 SAE J300
Density at 59 °F	0,88 g/cm ³ DIN 51757
Viscosity at 104 °F	200 mm ² /s ASTM D 7042-04
Viscosity at 212°F	20 mm ² /s ASTM D 7042-04
Viscosity at 14 °F (CCS)	<= 13000 mPas ASTM D 5293
Viscosity index	115 DIN ISO 2909
HTHS at 302 °F	>= 3,7 mPas ASTM D 5481
Pour point	-27 °F DIN ISO 3016
Evaporation loss (Noack)	4,6 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	6,9 mg KOH/g DIN ISO 3771
Sulfate ash	< 1,0 g/100g DIN 51575

Areas of application

For 4-stroke gasoline engines where a motor oil according to current product specifications is required or recommended, particularly suitable for Mercury Verado engines. Safe with or without catalytic converters and turbochargers.

Comment

⚠ WARNING: Reproductive Harm -
www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	22508 USA-EN
4 l Canister plastic	22510 USA-EN
205 l Black plate barrel	22514 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.