

Scratch Stop

Description

Scratch Stop is a grinding paste that does not contain silicone oil and is suitable for universal use. The product can be used to remove scratches, spray mist, stress marks and uneven finishes on colour or metallic paintwork. It is also suitable for matt and blank plastic discs or polycarbonate headlamp lenses, and can be used in both manual and automated processing.



Properties

- prepares surfaces for painting
- easy removal of weathered paint layers
- silicone-free
- simple to use

Technical data

Base	Abrasives, wax
Form	viscous
Color / appearance	violet
Odor	characteristic
Density	1,04 g/ml
Flash point	> 90 °C
Shelf life in original sealed container	30 months

Areas of application

Specially developed product for removing scratches. Suitable for colour and metallic paintwork. Optimally suited for processing matt and blank plastic discs or polycarbonate headlamp lenses.

Application

Wash the vehicle thoroughly before application. Shake the tube before use. Apply the product with a cloth or sponge and work it into the affected area under light pressure (polish with a foam buffing machine at 1,500 to 2,000 rpm). **Exercise caution during application on chassis joints, as the product is extremely abrasive.** Wipe off any polish residue using a clean cloth (preferably a microfibre cloth). After the procedure is completed, seal the paintwork surface using Universal Polish (part no. 1679).

Available pack sizes

200 ml Tube plastic 2320
D-GB-F-ARAB

Our information is based on thorough research and may be considered reliable, although not legally binding.