## **Product information**

# Marine 4T Motor Oil SAE 10W-40

### PI 33/12/09/2022



### **Description**

Fully synthetic, heavy duty motor oil. Provides outstanding wear protection, proper oil pressure and engine cleanliness. Optimum protection of engine components thanks to high content of anti-corrosion additives. Developed specifically for marine use. Meets major manufacturers requirements.

# SAE 10W-40 MOTOR OIL THE REAL PROPERTY OF THE REA

### **Properties**

- high wear resistance
- high engine cleanliness
- rapid oil penetration
- outstanding corrosion protection
- reliable cold start
- ideal with turbochargers and catalytic converters
- can be used in gasoline and diesel engines with and without turbocharger

### **Specifications / Approvals**

ACEA A3/B4, E7 • API SL • API CI-4 • Mack EO-N • Renault Trucks RI D-2 • Volvo VDS-3

# LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Caterpillar ECF-1-a • Caterpillar ECF-2 • Cummins CES 20071 • Cummins CES 20072 • Cummins CES 20076 • Cummins CES 20077 • Cummins CES 20078 • Detroit Diesel • Deutz DQC III-10 • MAN M 3275-1 • Mercury Marine • MTU Typ 2 • Selva • Suzuki Marine • Tohatsu • Yamaha

### **Technical data**

SAE class (engine oils)	10W-40 SAE J300
Density at 59 °F	0,865 g/cm³ DIN 51757
Viscosity at 104 °F	94 mm²/s ASTM D 7042-04
Viscosity at 212°F	14,5 mm²/s ASTM D 7042-04
Viscosity at -22 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -13 °F (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	160 DIN ISO 2909
HTHS at 302 °F	>= 3,5 mPas

ASTM D5481

-32 °F DIN ISO 3016

#### **Technical data**

Evaporation loss (Noack) 12,7 %

CEC-L-40-A-93

Flash point 446 °F

DIN ISO 2592

Total base number 10,5 mg KOH/g

DIN ISO 3771

Sulfate ash 1,0 - 1,6 g/100g

DIN 51575

Color number (ASTM) L4.0

**DIN ISO 2049** 

### Areas of application

For 4-stroke gasoline engines, where an oil according to current product specifications is required or recommended. Safe with catalytic converters and turbochargers.

### **Application**

Observe the manufacturers instructions!

### Available pack sizes

1 l Canister plastic 20506

USA-AND-CANADA-EN-F

4 l Canister plastic 20508

USA-AND-CANADA-EN-F

20 l Canister plastic 20496

USA-AND-CANADA-EN-F

60 l Black plate barrel 20497

USA-AND-CANADA-EN-F

205 l Black plate barrel 20498

USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Pour point

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com