Product information
Viscoplus for Oil

PI 41/11/02/2026



Description
Modern, mono-functional high-performance additive for stabilizing the viscosity of motor oils. Visco Plus offers outstanding protection against mechanical and therefore permanent shear losses to the oil under extreme running conditions and is effective against the thinning of motor oils due to frequent cold starts.

Properties
- reduces engine noise
- reduces oil consumption
- optimum oil pressure under all operating conditions
- stabilizes loss of viscosity
- optimum lubrication under all operating conditions
- fully compatible with mineral and synthetic oils
- improves the movable seal between piston and cylinder
- reduces wear

Technical data

Color / appearance	orange clear
Density at 20 °C	0,89 g/cm³ DIN 51757
Viscosity at 40 °C	299,6 mm²/s ASTM D7042
Flash point	120 °C DIN ISO 2592
Pour point	-15 °C DIN ISO 3016
Odor	characteristic
Form	liquid

Areas of application
For all cars and commercial vehicles, gasoline and diesel engines in new and used cars.

Comment
Not suitable for use on motorbikes with wet clutches!

Application
Can contents (300 ml) are sufficient for 5 liters of motor oil. After adding to the motor oil, allow the engine to run warm. The product can be added at any time.

Available pack sizes

300 ml Can sheet metal	1017 DE-FR-NL
300 ml Can sheet metal	2502 DE-ES-PT
300 ml Can sheet metal	2672 BG-DE-PL

Available pack sizes

300 ml Can sheet metal	2807 DA-FI-NO-SV
300 ml Can sheet metal	8362 AR-EN-FR
300 ml Can sheet metal	8377 DE-HU-RO
300 ml Can sheet metal	8958 EL-EN-IT
300 ml Can sheet metal	20916 JP
300 ml Can sheet metal	21695 AUEN-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com