

### Description

Synthetic high-performance grease with PTFE solid lubricants specially developed for all kinds of winching and hoisting applications. The solid lubricant provides the ultimate in wear protection and reduces friction. Resistant to fresh water and saltwater with excellent adhesive properties. Does not contain resins or acids.



### Properties

- excellent high-pressure and wear protection properties
- outstandingly adherent
- outstanding sea and salt water resistance
- ensures a long service life

### Technical data

Brief description	KHCF1N-35
Thickener	gel
Base	synthetic oil
Operating temperature range	-35 - +150 °C
Color / appearance	white
NLGI number	1 DIN 51 818
Dropping point	without DIN ISO 2176
Base oil viscosity 40°C	380 mm <sup>2</sup> /s DIN 51 562
Water resistance	0 DIN 51807

### Areas of application

Ideally suited for winching and hoisting applications with non-ferrous metal pairings or plastic/metal pairings. Powerful adhesive properties and neutral with respect to harmful environmental impact.

### Application

Before treating, the surfaces must be clean and free from residues, dirt and moisture.

### Available pack sizes

100 g Tube plastic	25045 D-F-I-E-GR
100 g Tube plastic	25046 GB-DK-N-FIN-S-RUS

**Our information is based on thorough research and may be considered reliable, although not legally binding.**