

### Description

Ash-free, self-mixing combination of active agents according to the latest additive, fuel and engine technology. Specially developed to satisfy the demands and operating conditions of today's engines. Prevents corrosion problems in the fuel system and thus prevents operational malfunctions.

### Properties

- binds and removes water
- good corrosion protection
- tested for turbochargers and catalytic converters
- environmentally friendly
- prevents carburetor icing
- economical

### Technical data

Base	additives, special carrier fluid
Color / appearance	clear, yellowish
Density at 15 °C	0,8 g/ml
Density at 20 °C	0,79 g/ml
Refractive index at 20 °C	1,38
Form	liquid
Viscosity at 40 °C	< 7 mm <sup>2</sup> /s
Odor	characteristic

### Areas of application

For all gasoline engines, specifically when used with fuels slightly contaminated with water.

### Application

Add to fuel whenever filling up. 300 ml sufficient for 60 l fuel.

### Available pack sizes

300 ml Can sheet metal	2530 GB-ARAB-F
300 ml Can sheet metal	2811 DK-N-S-FIN
300 ml Can sheet metal	2955 GB-GR-I
300 ml Can sheet metal	8356 D-E-P
5 l Canister plastic	2855 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

