Product information
Fuel Protect Gasoline

PI 29/10/30/2026



Description
Ash-free, self-mixing combination of active agents based on the latest additive, fuel, and engine technology. Specially developed to satisfy the demands and operating conditions of today's engines. Prevents corrosion problems in the fuel system and thus prevents operational malfunctions.

Properties
- good corrosion protection
- binds and removes water
- tested for turbochargers and catalytic converters
- prevents carburetor icing
- economical

Technical data

Base	additives, special carrier fluid
Color / appearance	clear, yellowish
Density at 15 °C	0,8 g/ml
Density at 20 °C	0,79 g/ml
Refractive index at 20 °C	1,38
Form	liquid
Viscosity at 40 °C	< 7 mm²/s
Odor	characteristic

Available pack sizes

300 ml Can sheet metal	2530 AR-EN-FR
300 ml Can sheet metal	2955 EL-EN-IT
300 ml Can sheet metal	8356 DE-ES-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com