Product information
Hydraulic Lifter Additive

PI 51/11/24/2026



Description

Prevents and reduces hydraulic lifter noise. Cleans oil passages to remove oil flow restrictions. Restores proper hydraulic lifter function and reduces wear.

- damps hydraulic tappet noise
- cleans valve bores
- improves the lubrication properties of the oil

Properties

- ideal with turbochargers and catalytic converters
- dampens hydraulic lifter noise
- cleans oil passages
- improves the lubrication properties

Technical data

Color / appearance	orange, klar
Density at 68 °F	0,887 g/cm³ DIN 51757
Form	liquid
Odor	characteristic
Viscosity at 68 °F	1100 mPas

Areas of application

For all 4-stroke gasoline and diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF/DPF). Compatible with most commercially available motor oils and belt-in-oil systems.

Comment

Not suitable for use on motorbikes with wet clutches.

Application

One full can (300 ml) used with 3–6 Liters (3.2 to 6.4 U.S. Qts) of motor oil. The product is self-mixing and can be added at any time. Shake well before use. For best results, use with every oil change.

Available pack sizes

300 ml Can sheet metal	20004 USEN
300 ml Can sheet metal	20330 CAEN-CAFR

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com