Product information

Gear Tronic II

PI 7/12/02/2021



Description

Fully automatic ATF oil changing device with the most up-to-date control technology for automatic transmission systems. Intuitive operation thanks to self-explanatory, user-friendly menu guidance. Universal device suitable for use with all makes of car. After the integrated cleaning program is applied, a high level of functionality is guaranteed even with extremely dirty transmissions. The exceptional accuracy of the liquid exchange process is realized through the use of two independent scales. Data concerning the total fill quantity, type and density of the automatic transmission fluid, tightening torques of the oil sump, drain plug and checking screws and the vehicle manufacturer, vehicle type and engine size can be retrieved free of charge using the integrated database. The data are documented using an integrated printer. Contains the following accessories: Gear Tronic Adapter Kit Standard 01 (part no. 29021).



Areas of application

Suitable for all converter gears, automatic continuously variable transmissions and dual clutch transmissions. Specially designed for the professional replacement of transmission fluids. Enables the change to be made via the cooler as well as the dipstick mode including cleaning.

Comment

Tank capacity: 25 liters

Additive capacity: 0.5 liters

Pump capacity: 10 l/min

Outer dimensions: 1020 x 750 x 650 mm (H x W x D)

Weight: 65 kg

Application

More detailed information about the device and its operation can be found in the operating instructions or the application video.

Available pack sizes

29066 1 pcs Carton

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com