

## Octane Plus

### Description

Self-mixing combination of active agents for universal use. Increases the research octane number (RON) of the fuel by 2 – 4 points, depending on the RON. Prevents engine damage due to knocking combustion by improving the performance of the fuel and ensures lower fuel consumption thanks to the increased octane number.



### Properties

- improves performance
- increases the octane number
- prevents engine damage caused by knocking combustion

### Technical data

Color / appearance	brown, clear
Base	additives, naphtha
Density at 15 °C	0,817 g/cm <sup>3</sup>
Flash point	63 °C
Pour point	-45 °C
Viscosity at 40 °C	< 7,0 mm <sup>2</sup> /s
Odor	characteristic
Form	liquid

### Available pack sizes

200 l Black plate barrel 8858  
D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Areas of application

For increasing the octane number of gasolines in vehicles without particulate filters.

### Comment

**Attention:** Only available for order outside Europe.

### Application

150 ml sufficient for 50 l gasoline. Fill directly into the tank and then refuel. Mixing takes place automatically.

**Note:** Do not store the product at temperatures > 39 °C for extended periods!

### Available pack sizes

150 ml Can sheet metal	2956 GB-GR-I
150 ml Can sheet metal	7144 ALGERIEN-GB-ARAB-F
150 ml Can sheet metal	8351 GB-ARAB-F
150 ml Can sheet metal	8355 D-E-P
150 ml Can sheet metal	21888 GB-P-E-RUS-UA-ARAB
150 ml Can sheet metal	21993 MX