

Motorbike 2T Synth Offroad Race**Description**

Fully synthetic high-performance 2-stroke motor oil developed and tested on racing machines. Ensures maximum performance and protection of the engine in all operating conditions. Outstanding lubrication and engine cleanliness, excellent friction behavior and minimized wear as well as less smoke. This oil improves the riding experience!

**Properties**

- high wear resistance
- residue-free combustion
- prevents the build-up of deposits
- high thermal stability
- good corrosion protection
- self mixing

Approvals

API TC • Husqvarna • ISO L-EGD • JASO FD

Technical data

Density at 59 °F	0,875 g/cm ³ DIN 51757
Viscosity at 104 °F	50 mm ² /s ASTM D 7042-04
Viscosity at 212°F	9,1 mm ² /s ASTM D 7042-04
Viscosity index	165 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016
Flash point	208 °F DIN ISO 2592
Total base number	2,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,15 g/100g DIN 51575
Color / appearance	red

Areas of application

For air or water cooled 2-stroke gasoline engines where an oil according to current product specifications is required or recommended. Self-mixing. Pre-mix applications up to 1:100 ratio and according to the manufacturers instructions.

Comment

⚠ WARNING: Cancer- www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Available pack sizes

1 l Canister plastic	20178 USA-AND-CANADA-EN-F
4 l Canister plastic	20180 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.