

Description

Part synthetic high-performance 2-stroke motor oil. Ensures optimum performance and protection of the engine in all operating conditions. Reliable lubrication, best engine cleanliness, excellent friction and minimum wear as well as low smoke.



Properties

- guarantees clean spark plugs
- burns ash-free
- self mixing
- good corrosion protection
- residue-free combustion
- high wear resistance

effectiveness only when the product is used in undiluted form.

Available pack sizes

1 l Canister plastic	20182
	USA-AND-CANADA-EN-F
4 l Canister plastic	20184
	USA-AND-CANADA-EN-F

Approvals

API TC • ISO L-EGC • JASO FC • TISI (Thailand International Standards Institute)

Technical data

Density at 59 °F	0,865 g/cm ³ DIN 51757
Viscosity at 104 °F	59,5 mm ² /s ASTM D 7042-04
Viscosity at 212°F	9,1 mm ² /s ASTM D 7042-04
Viscosity index	130 DIN ISO 2909
Pour point	-11 °F DIN ISO 3016
Flash point	230 °F DIN ISO 2592
Total base number	1,1 mg KOH/g DIN ISO 3771
Sulfate ash	0,06 g/100g DIN 51575
Color / appearance	red

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

For air or water cooled 2-stroke gasoline engines where an oil according to current product specifications is required or recommended. Self-mixing. Pre-mix applications up to 1:50 ratio and according to the manufacturers instructions.

Comment

⚠ **WARNING:** Cancer- www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions! Optimum