

ATV Axle Oil 10W-30

Description

High-performance high-pressure gear oil made from carefully selected base oils and multifunctional additives. The oil can therefore be used in a wide range of transmissions and drives. Outstandingly suitable for assemblies with a wet clutch and/or wet brake.

Properties

- reduces running noise
- very compatible with seals
- especially suitable for wet clutches
- minimizes wear
- excellent resistance to aging
- excellent viscosity/temperature properties
- high pressure-absorption capability

Specifications / Approvals

API GL4

Technical data

SAE class (engine oils)	10W-30 SAE J300
SAE class (gear oils)	80W SAE J306
Density at 15 °C	0,860 g/cm ³ DIN 51757
Viscosity at 40 °C	50,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,6 mm ² /s ASTM D 7042-04
Viscosity at -25 °C	< 7000 mPas DIN 51377
Viscosity at -35 °C	< 70000 mPas ASTM D 2983
Viscosity index	180 DIN ISO 2909
Pour point	-39 °C DIN ISO 3016
Flash point	230 °C DIN ISO 2592
Foaming behavior at 24 °C	0/0 ml ISO 6247
Foaming behavior at 93.5 °C	40/0 ml ISO 6247
Foaming behavior at 24 °C after 93.5 °C	0/0 ml ISO 6247
Color number (ASTM)	2,0 DIN ISO 2049



Areas of application

For transmissions and final drives with and without a wet clutch and/or wet brake operating under normal to high load.

Application

The transmission manufacturer's instructions must be followed. Can be mixed with all branded gear oils. Fully effective only when used alone.

Available pack sizes

1 l Can plastic	3094 D-GB-I-E-P
1 l Can plastic	5930 D-F-I-GR

Our information is based on thorough research and may be considered reliable, although not legally binding.