

Wax Coating

Description

Extremely adherent, wax-based corrosion protection containing state-of-the-art agents. The adherent, permanently elastic and transparent protective film offers outstanding, reliable long-term protection for inside and outside storage. Resistant to salt water and corrosive environments. The thin coating does not impair any subsequent welding work.



and may be considered reliable, although not legally binding.

Properties

- outstanding resistance to salt water
- excellent corrosion protection
- excellent long-term protection
- can be used indoors and outdoors
- transparent, adherent and waterproof protective film

Technical data

Base	wax, solvents
Appearance / properties	light brown
Propellant	propane, butane
Film thickness	15-50 µm
Form	aerosol, liquid
Odor	characteristic

Areas of application

For inside and outside storage, transport and dispatch of machines and metal components.

Application

Shake can well before use. Application on clean, dry surface by spraying. The coat thickness is between 15 µm and 50 µm, depending on environmental conditions. Apply several coats to increase protection against corrosion. The contents of the can should be at room temperature during application. When spraying in enclosed spaces, make sure that there is sufficient ventilation. After use, clear spray nozzle (hold can with spray head upside down) by spraying until only pure propellant emerges.

Note: LIQUI MOLY Engine Compartment Cleaner (part no. 3326) can be used for removal of the wax coating. The application notes can be found in its product information.

Available pack sizes

300 ml Can aerosol 3311
D-GB-E-P

Our information is based on thorough research