

Top Tec ATF 1900

Description

The next generation of high-performance automatic transmission fluid based on selected base oils and state-of-the-art, powerful additive components. The reduced viscosity contributes to the reduced consumption and the increased effectiveness. Thanks to the outstanding stability of the friction coefficient, extended oil change intervals are possible.



Properties

- reduces fuel consumption
- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

MB 236.15

Technical data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	19 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	4,4 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 10000 mPas ASTM D 2983-09
Viscosity index	148 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	190 °C DIN ISO 2592
Color / appearance	blue to green

Areas of application

Developed for Mercedes-Benz 7-speed automatic transmissions of type 722.9 and 724.2 (hybrid).

Application

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. Cannot be mixed with oils of other specifications.

Available pack sizes

1 l Can plastic	3648 D-GB-I-E-P
-----------------	--------------------

Available pack sizes

1 l Can plastic	21267 ALGERIEN-GB-ARAB-F
1 l Can plastic	21683 GB-DK-FIN-N-S
20 l Canister plastic	3649 D-GB-I-E-P
60 l Black plate barrel	20615 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.