# **Product information**

# Motorbike Speed Shooter

# PI 40/11/24/2023



### **Description**

A unique, state-of-the-art combination of acceleration-enhancing, cleaning, dispersing and material-protecting additives. Easy engine start, smoother running and better throttle response are the effects.

#### **Properties**

- good corrosion protection
- residue-free combustion
- quarantees optimum combustion
- improves acceleration
- removes deposits from entire fuel system
- highly economical
- prevents carburetor icing
- higher performance gain

#### Technical data

Base additive mixture in

carrier fluid

Color / appearance yellow, clear

Odor characteristic

Form liquid
Viscosity at 104 °F <7 mm²/s
Density at 68 °F 0,814 g/cm³

Hazard class as per

German VbF

A III

Flash point >61 °F

#### Areas of application

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters.

#### Comment

▲ WARNING: Cancer- www.P65Warnings.ca.gov

## **Application**

Contents (80 mL) is sufficient for 5–10 Liters (1.3 gal. to 2.6 gal.) gasoline. Add at every fill-up.

#### Available pack sizes

80 ml Can sheet metal 20140

**USA-EN** 

80 ml Can sheet metal 20346

CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not

## legally binding.



Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de