

### Description

High-performance hydraulic oil made from high-quality raffinates. Thanks to the high thermal stability of the base oils, the aging process is significantly reduced even at elevated temperatures. This decisively helps reduce the formation of sludge, improves cleanliness and promotes the reliability of the hydraulic systems. Excellent oxidation resistance permits lengthy oil life (changing intervals). The outstanding wear-protection technology is effective in both low and high load conditions. Good corrosion protection behavior even if water is present. The hydraulic components are thus optimally protected in all operating conditions.

### Properties

- high resistance to aging
- good corrosion protection
- highest thermal stability
- high wear resistance

### Approvals

Hydrauliköl DIN 51524 Teil 2 HLP 10

### Technical data

ISO viscosity class	VG 10 DIN 51519
Viscosity at 104 °F	10 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	2,7 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	108 DIN ISO 2909
Density at 59 °F	0,84 g/cm <sup>3</sup> DIN 51757
Pour point	-27 °F DIN ISO 3016
Flash point	334 °F DIN ISO 2592
Demulgation characteristics at 129 °F	<10 min DIN ISO 6614
Air separation capacity	2 min DIN ISO 9120
Foaming behavior at 75 °F	30/0 ml ISO 6247
Foaming behavior at 200 °F	50/0 ml ISO 6247
Foaming behavior at 75 °F after 200 °F	30/0 ml ISO 6247
Corrosion effect on steel	0-B DIN ISO 7120



### Technical data

Corrosion effect on copper	1-125 A3 DIN EN 2160
Neutralization number	0,5 mg KOH/g DIN 51558 T1
Neutralization number after 1000 h	< 2 mg KOH/g DIN 51587
Oxide ash	0,16 g/100g DIN EN ISO 6245
Sulfate ash	0,17 g/100g DIN 51575
Color number (ASTM)	0,5 DIN EN ISO 2160

### Areas of application

For stationary and mobile applications in hydraulic systems in construction, forestry and agricultural machinery such as excavators, tractors etc., hoists, industrial machinery and machine tools, wood splitters, lifting platforms and presses, etc. Thanks to its good compatibility with materials, this LIQUI MOLY hydraulic oil can be used in the most common pump systems in hydraulic systems. This hydraulic oil can also be used with all mineral-oil-compatible sealing materials and coatings.

### Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

20 l Canister plastic	4130 D-GB
-----------------------	--------------

**Our information is based on thorough research and may be considered reliable, although not legally binding.**