# **Product information**

# ATF Dexron II D

# PI 24/04/20/2024



## **Description**

Automatic transmission fluid with excellent aging stability. Prevents the build-up of troublesome deposits. For vehicles with proven transmission technology. Maximum protection against wear and good friction characteristics. Good seal compatibility. Provides optimum protection against corrosion.

### **Properties**

- friction and wear reducing
- excellent viscosity/temperature properties
- outstanding corrosion protection
- very good low-temperature properties
- highest thermal stability
- high chemical resistance
- optimum stability to aging

# **Specifications / Approvals**

Allison C4 • Denison • Dexron II D • Ford ESP-M2C 166-H • GM -Dexron • MAN 339 Typ L2 • MAN 339 Typ V1 • MAN 339 Typ Z1 • Voith H55.6335.XX (G 607) • ZF TE-ML 04D • ZF TE-ML 11A • ZF TE-ML 14A • ZF approval number ZF002052

# LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Caterpillar TO-2 • MB 236.6 • ZF TE-ML 09 • Ford Mercon

#### Technical data

Density at 15 °C 0,855 g/cm<sup>3</sup> DIN 51757 Viscosity at 40 °C 46 mm<sup>2</sup>/s ASTM D 7042-04 Viscosity at 100 °C 8,3 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -40 °C <= 50000 mPas (Brookfield) ASTM D 2983-09

Viscosity index 157

**DIN ISO 2909** 

-42 °C Pour point

**DIN ISO 3016** 

206 °C Flash point

**DIN ISO 2592** 

Oxide ash  $0.22 \, \text{g}/100 \, \text{g}$ 

**DIN EN ISO 6245** 

Sulfate ash  $0.3 \, q/100 q$ 

DIN 51575 6,1 mm<sup>2</sup>/s

Shear stability, viscosity at

100 °C after 20 h DIN 51350-06 KRL/C

#### Technical data

Color / appearance rot

#### Areas of application

ATF Dexron IID is used in numerous mechanic manual transmissions, automatic transmissions, in torque converters and in numerous power steering systems in accordance with the specifications and operating instructions specified by the motor vehicle and transmission manufacturers.

# **Application**

The instructions from the unit or automobile manufacturer must be followed. Miscible with commercially available Dexron II D type ATF oils. However, the optimum performance is only guaranteed when the product is used on its own.

#### Available pack sizes

4443 1 l Can plastic

D-GB-I-E-P

4424 20 l Canister plastic

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de