Description

Highly effective cleaning fluid designed to dissolve problematic deposits and residues in automatic transmissions for optimum shifting performance, thus extending the transmission service life. These highly effective detergent and dispersant additives in association with the carrier fluid have been tested in the laboratory and in practical field trials for their ability to dissolve sludge and lacquer formers.

additive, naphtha-base special

Properties

- gentle cleaning
- assures optimum shifting performance
- does not attack rubber and plastic seals

oil

204 58 mm²/s

11,8 mm²/s

flüssig, liguid

characteristic

- optimizes economical use
- easily dissolves stubborn dirt

Technical data

Viscosity index

Viscosity at 40 °C

Viscosity at 100 °C

Base

Form

Odor

Density at 15 °C 0,885 g/ml

Areas of application

Suitable for all automatic transmissions and power steering systems without an additional system. 300 ml are sufficient for 6-9 l of ATF.

Application

Add the appropriate amount of the can contents to the gear oil and then run the engine for 10 – 15 minutes at idle speed. Shift through all gears once or twice. Then stop the engine and change the oil and the oil filter. For optimum effect we recommend the use of our automatic transmission service device Gear Tronic.

Available pack sizes

1 l Can sheet metal	5101
	D-GB-I-E-P
5 l Canister plastic	5179
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not





