

Liquifast 9000 (Bag-set)

Description

Cold-application, moisture-curing, 1-component polyurethane adhesive for bonding front, rear and side windows on vehicles in the case of repairs. An adhesive of this type is prescribed in particular if the vehicle windows can be heated or vehicle antennas have been integrated into the window. Is characterized by very high initial strength (high tack effect). This enables even high adhesive beads to be applied cleanly and prevents heavy or slanted windshields from sinking or slipping immediately after bonding. The high shear modulus contributes to significantly increased torsional stiffness, greater driving safety and higher driving comfort. The low electrical conductivity of the adhesive prevents potential contact corrosion on the body. It can be processed at temperatures from -15 °C (!) with 30 min. standstill and drive-away time, which allows the application even under unfavorable weather conditions. TÜV tested.



Technical data

Base	Polyurethanpräpolymere
Color / appearance	black
Density	ca. 1,130 g/cm ³ DIN 53217-4
Rigidity	very good
Processing temperature	15 - 35 °C
Skin formation time at 23 °C/50 % relative humidity	ca. 12 - 15 min
Processing time at 23 °C/50 % relative humidity	ca. 13 min
Curing rate at 23 °C / 50 % rh	ca. 3.5 - 4 mm/24h
Hardness, Shore A	ca. 61 DIN 53 505
Tensile strength	ca. 10 MPa DIN 53504
Elongation at break	ca. 500 % DIN 53504
Tear propagation	ca. 12 N/mm DIN 53515
Combined tension and shear resistance	ca. 7 MPa DIN EN 1465
G modulus (shear modulus)	ca. 2,5 MPa DIN 54451
Volume resistance	ca. 10 ⁷ Ω · cm DIN 60093
Thermal stability	< 80 °C

Technical data

Thermal stability, short-term (up to 1 hour)	< 120 °C
Drive-away time	30 min ohne Airbag / without airbag
Drive-away time	30 min mit Doppel-Airbag / with double-airbag
Shelf life in original sealed container	18 months
Recommended storage temperature	0 - 35 °C

Areas of application

For gluing front, rear and side windows into the bodywork of motor vehicles (cars, trucks, drivers' cabins of tractors/forklifts and special vehicles) as well as for gluing side windows made from a single pane and insulation glass in bus and train car construction.

Comment

Recommendations for use are provided in the accompanying brochure!
Set shelf life: 12 months

The best before date and technical data for the individual products are provided in the relevant product information.

Application

1. Cleaner

The surfaces to be bonded must be dry, free from oil, dust, grease and other dirt residues. The complete pane must be cleaned on the inside with our Windshield Cleaner Foam (part no. 1512). Then clean the bonding surface with Liquiclean (part no. 6186) or Cleaner and Thinner (part no. 6130), as well as the body flange or newly painted body components. We recommend cleaning the cut-back residual adhesive bead with Liquiclean or Cleaner and Thinner as well. Before applying the sealant or bonding the window,

Liquifast 9000 (Bag-set)

the cleaned bonding surface must be completely dry.

Note: To enable optimum adhesion to the body flange, we recommend cleaning the body flange thoroughly before trimming back. Cut back the remaining bead as far as possible.

2. Priming/activation of pre-coated windows

Active Primer is required for adhesive pre-treating during window bonding. The Active Primer is included in the scope of delivery of the Window Repair Kit as a 10 ml stick. Shake Active Primer well for at least 45 seconds before use. Active Primer can be applied universally in the bonding area thinly and evenly (approx. 0.05 mm wet-film thickness) on the cleaned glass surface or ceramic screen printing, on the clean paint surface of newly painted car-body components, on remaining adhesive beadings that have been trimmed back and pre-coated windows (PUR and RIM coatings). The primed surface must be allowed to air off for at least 10 min. (23 °C/ 50 % RH) applying the windshield adhesive. If the residual adhesive bead was cut back more than 6 hours ago, pre-treatment with Active Primer is mandatory.

The application recommendations can be found in the enclosed brochure!

Available pack sizes

1 pcs Carton 6028
D-GB-F-I-E-NL-P

Our information is based on thorough research and may be considered reliable, although not legally binding.