

Product information

Cable Grease (Spray)

PI 25/09/15/2023



Description

High-quality lubricant for the preservation of wire cables. Thanks to its excellent corrosion protection, it is also suitable for cavity sealing and underfloor protection in the automotive sector.

Properties

- excellent corrosion protection
- drives out moisture
- has a lasting effect
- excellent penetration action
- highest load-carrying capacity
- optimum effectiveness when the product is used unmixed
- no aromatic hydrocarbons
- silicone-free
- high bond strength



and may be considered reliable, although not legally binding.

Technical data

Color / appearance	brown
Dropping point	> 85 °C
Base	additives, polymers
Viscosity at 40 °C	22 mm ² /s
Form	aerosol, liquid
Odor	characteristic
Shelf life in original sealed container	30 months
Recommended storage temperature	10 - 30 °C

Areas of application

For preventive preservation of wire cables. Also suitable for the cavity sealing and underfloor protection of vehicles.

Application

The parts to be treated must be dry and free of dirt and rust. Shake well before use. The aerosol is sprayed onto the cables. After use, the valve of the can should be sprayed empty upside down until only propellant gas escapes!

Use of the Cavity Seal Spray Probe (part no. 6208) is possible.

Available pack sizes

500 ml Can aerosol 6135
D-GB-I-E-P

Our information is based on thorough research