

Product information

Meguin Gleitoel CGLP 220



Description

Lubricant with outstanding lubrication properties. Selected base oils combined with up-to-date additive technology guarantee the optimum anti-wear properties, prevent stick-slip and provide the highest level of adherence even under mixed friction conditions. Predominantly used as a machine tool oil, slideway oil and for lubricating heavy-duty reciprocating frame saws. It stands out in particular for its good demulsification capacity in relation to cooling lubricants.

Approvals

Schmieröl DIN 51502 CGLP 220

Characteristic data

ISO viscosity class	VG 220 DIN 51519
Density at 15 °C	0,895 g/cm ³ DIN 51757
Viscosity at 40 °C	220 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	19,5 mm ² /s ASTM D 7042-04
Viscosity index	100 DIN ISO 2909
Pour point	-18 °C DIN ISO 3016
Flash point	260 °C DIN ISO 2592
Foaming behavior at 24 °C	0/0 ml ISO 6247
Foaming behavior at 93.5 °C	0/0 ml ISO 6247
Foaming behavior at 24 °C after 93.5 °C	0/0 ml ISO 6247
Neutralization number	1,4 mg KOH/g DIN 51558 T1
Sulfate ash	0,3 g/100g DIN 51575
Corrosion effect on steel	0-A DIN ISO 7120
Corrosion effect on copper	1-100 A3 DIN EN ISO 2160
FZG gear rig test, standard test A/8, 3/90	Schadenskraftstufe >12, Spez.Gew.Änderung <0,3 mg/KWh DIN 51354 Teil 2
Color number (ASTM)	L 4,0 DIN ISO 2049

Available pack sizes

20 l Canister plastic	6535 D-GB
200 l Drum sheet metal	8657 D-GB
1.000 l Deposit container	9536 D-GB

Available pack sizes