

Product information

megol Gasmotorenoel High Performance SAE 40



Description

Gas motor oil with increased ash content and distinct quality reserve. For a wide range of applications. Offers good wear and corrosion protection, high acid neutralization capacity as well as excellent oxidation and temperature stability thanks to selected base oils and the specially developed additive package. Ideally suited for operation with natural gas, sewage gas and landfill gas. Achieves very good operating results when using biogas due to its increased acid neutralization capacity. Also suitable for dual operation with liquid and gaseous fuels. The specifications and instructions from the assembly or machine manufacturer must be followed.



Meguin also recommends this product for vehicles that are subject to the following specifications

MAN M 3271-4

Characteristic data

Density at 15 °C	0,88 g/cm ³ DIN 51757
Viscosity at 40 °C	150 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	15,5 mm ² /s ASTM D 7042-04
Viscosity index	105 DIN ISO 2909
Flash point	240 °C DIN ISO 2592
Pour point	-24 °C DIN ISO 3016
Total base number	9,6 mg KOH/g DIN ISO 3771
Sulfate ash	0,92 g/100g DIN 51575
SAE class (engine oils)	40 SAE J300

Available pack sizes

200 l Drum sheet metal	8711 D-GB
1 l Bulk goods	8465 D-GB