Product information

Meguin Spindeloel N 10



Description

Aging-resistant mineral oil without added agents. Predominantly for lubrication points with once-through and circulation lubrication systems. In metalworking also applicable as an excellent cutting and cooling oil for light to moderate machining procedures.

Specification:
Lubricating oil DIN 51501 – L-AN 10

Characteristic data

ISO viscosity class	VG 10 DIN 51519
Density at 15 °C	0,84 g/cm³ DIN 51757
Viscosity at 40 °C	10 mm²/s ASTM D 7042-04
Viscosity at 100 °C	2,7 mm²/s ASTM D 7042-04
Viscosity index	108 DIN ISO 2909
Pour point	-24 °C DIN ISO 3016
Flash point	160 °C DIN ISO 2592
Neutralization number	0,05 mg KOH/g DIN 51558 T1
Saponification number	0,08 mg KOH/g DIN 51559 T1
Oxide ash	<0,01 g/100g DIN EN ISO 6245
Color number (ASTM)	L 1,0 DIN ISO 2049

Areas of application

Available pack sizes

200 l Drum sheet metal	8727 D-GB

Meguin GmbH & Co. KG
Mineraloelwerke

Rodener Str. 25
D-66740 Saarlouis
Germany

Phone: +49 (0)6831/8909-0
Fax: +49 (0)6831/8909-59
e-mail: vertrieb@meguin.de