

Product information

Meguín Rostschutz-Sprühoel mit Graphit



Description

Thin mineral oil with corrosion protection additive that atomises quickly and easily. It penetrates all metal gaps and folds extremely well and spreads over the base of the treated vehicle. The film that forms is not aggressive towards rubber parts and noiseinsulating bitumen compounds. Its special additives protect the metal parts against rust and also act as an anti-squeal fluid between chafing metal parts and leaf springs. This effect is enhanced even further by the graphite in the oil which reduces friction.

Characteristic data

ISO viscosity class	VG 7 DIN 51519
Density at 15 °C	0,83 g/cm ³ DIN 51757
Viscosity at 20 °C	17,3 mm ² /s ASTM D 7042-04
Viscosity at 40 °C	8,9 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	2,5 mm ² /s ASTM D 7042-04
Viscosity index	107 DIN ISO 2909
Pour point	-30 °C DIN ISO 3016
Flash point	150 °C DIN ISO 2592
Neutralization number	0,2 mg KOH/g DIN 51558 T1
Saponification number	1,6 mg KOH/g DIN 51559 T1
Oxide ash	0,01 g/100g DIN EN ISO 6245
Color / appearance	schwarz

Available pack sizes

20 l Canister plastic	8755 D-GB
-----------------------	--------------