Product information

Meguin Heissdampf Zylinderoel ZB 1000



Description

Pure mineral oil primarily used to lubricate the sliding parts of steam engines that are in contact with steam and whose steam temperatures do not exceed 325 °C. Also suitable as a high viscosity lubricating oil for lubrication points with feed-through lubrication systems.

Specifications:
Lubricating oil ZB DIN 51510

Characteristic data

ISO viscosity class	VG 1000 DIN 51519
Density at 15 °C	0,9 g/cm³ DIN 51757
Viscosity at 40 °C	1000 mm²/s ASTM D 7042-04
Viscosity at 100 °C	53 mm²/s ASTM D 7042-04
Viscosity index	100 DIN ISO 2909
Pour point	-12 °C DIN ISO 3016
Flash point	280 °C DIN ISO 2592
Oxide ash	0,1 g/100g DIN EN ISO 6245
Color number (ASTM)	L 4,0 DIN ISO 2049

Available pack sizes

200 l Drum sheet metal	8762 D-GB

Meguin GmbH & Co. KG
Mineraloelwerke

Rodener Str. 25
D-66740 Saarlouis
Germany

Phone: +49 (0)6831/8909-0
Fax: +49 (0)6831/8909-59
e-mail: vertrieb@meguin.de