

## 2005 DIESEL PURGE, 500ml

Liqui Moly GmbH

Chemwatch Hazard Alert Code: 1

Chemwatch: 94-3242

Issue Date: 01/11/2019

Version No: 3.1.1.1

Print Date: 14/04/2020

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

S.GHS.U.S.A.EN

### SECTION 1 IDENTIFICATION

#### Product Identifier

Product name	2005 DIESEL PURGE, 500ml
Synonyms	Not Available
Other means of identification	Not Available

#### Recommended use of the chemical and restrictions on use

Relevant identified uses	System cleaner for vehicle fuel units (diesel engines).
--------------------------	---

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Liqui Moly GmbH
Address	Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
Telephone	+49 731 1420 0
Fax	+49 731 1420 82
Website	<a href="http://www.liqui-moly.com/">http://www.liqui-moly.com/</a>
Email	Not Available

#### Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	+1800 535 5053 (US, Canada & Mexico)
Other emergency telephone numbers	+1 352 323 3500 (International)

### SECTION 2 HAZARD(S) IDENTIFICATION

#### Classification of the substance or mixture

##### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	1	1
Toxicity	1	1
Body Contact	1	1
Reactivity	1	1
Chronic	0	0

##### NFPA 704 diamond



0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Flammable Liquid Category 4, Eye Irritation Category 2B, Aspiration Hazard Category 1, Chronic Aquatic Hazard Category 2
----------------	--

#### Label elements

Hazard pictogram(s)	
---------------------	--

SIGNAL WORD	<b>DANGER</b>
-------------	---------------

#### Hazard statement(s)

H227	Combustible liquid.
H320	Causes eye irritation.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

**Hazard(s) not otherwise classified**

Not Applicable

**Precautionary statement(s) Prevention**

<b>P210</b>	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
<b>P273</b>	Avoid release to the environment.
<b>P280</b>	Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement(s) Response**

<b>P301+P310</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
<b>P331</b>	Do NOT induce vomiting.
<b>P370+P378</b>	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Precautionary statement(s) Storage**

<b>P403+P235</b>	Store in a well-ventilated place. Keep cool.
<b>P405</b>	Store locked up.

**Precautionary statement(s) Disposal**

<b>P501</b>	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
64742-48-9.	>80	<u>Naphtha (petroleum), hydrotreated heavy</u>
27247-96-7	5-15	<u>2-ethylhexyl nitrate</u>
64742-94-5	0.1-<1	<u>solvent naphtha petroleum, heavy aromatic</u>

**SECTION 4 FIRST-AID MEASURES****Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul>

**Most important symptoms and effects, both acute and delayed**

See Section 11

**Indication of any immediate medical attention and special treatment needed**

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- ▶ Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.

Continued...

- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
  - ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
  - ▶ Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]
- Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

## SECTION 5 FIRE-FIGHTING MEASURES

### Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

### Special protective equipment and precautions for fire-fighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) nitrogen oxides (NO<sub>x</sub>) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.</p>

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> </ul>
<b>Major Spills</b>	<p>Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

<b>Safe handling</b>	<p>The conductivity of this material may make it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.</p> <ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ Electrostatic discharge may be generated during pumping - this may result in fire.</li> <li>▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment.</li> <li>▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (&lt;= 1 m/sec until fill pipe submerged to twice its diameter, then &lt;= 7 m/sec).</li> <li>▶ Avoid splash filling.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>
<b>Storage incompatibility</b>	▶ Avoid reaction with oxidising agents, bases and strong reducing agents.

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION****Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	Naphtha (petroleum), hydrotreated heavy	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	Naphtha (petroleum), hydrotreated heavy	Oil mist, mineral	5 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	Naphtha (petroleum), hydrotreated heavy	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m <sup>3</sup>	Not Available	Not Available	URT irr

**EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Naphtha (petroleum), hydrotreated heavy	Naphtha, hydrotreated heavy; (Isopar L-rev 2)	350 mg/m <sup>3</sup>	1,800 mg/m <sup>3</sup>	40,000 mg/m <sup>3</sup>


Ingredient	Original IDLH	Revised IDLH
Naphtha (petroleum), hydrotreated heavy	2,500 mg/m <sup>3</sup>	Not Available
2-ethylhexyl nitrate	Not Available	Not Available
solvent naphtha petroleum, heavy aromatic	Not Available	Not Available

**OCCUPATIONAL EXPOSURE BANDING**

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
2-ethylhexyl nitrate	E	≤ 0.1 ppm

**Notes:** Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

**Exposure controls**

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p> <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C. apron.</li> <li>▶ Barrier cream.</li> </ul>

**Respiratory protection**

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Appearance</b>	Light brown, clear liquid with characteristic odour; not miscible with water.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.816
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	<7
<b>Initial boiling point and boiling range (°C)</b>	180	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	63	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Combustible.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	6	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	0.7	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Immiscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	>1	<b>VOC g/L</b>	Not Available

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

<b>Inhaled</b>	<p>There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p>
<b>Ingestion</b>	<p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p>
<b>Skin Contact</b>	<p>The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>The material may accentuate any pre-existing dermatitis condition</p>

	Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
<b>Eye</b>	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
<b>Chronic</b>	There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.
<b>2005 DIESEL PURGE, 500ml</b>	<b>TOXICITY</b>
	Dermal (None) LD50: >2000 mg/kg <sup>[2]</sup>
	Inhalation (None) LC50: >20 mg/m <sup>3</sup> /4h <sup>[2]</sup>
	Oral (None) LD50: >2000 mg/kg <sup>[2]</sup>
<b>Naphtha (petroleum), hydrotreated heavy</b>	<b>TOXICITY</b>
	Dermal (rabbit) LD50: >1900 mg/kg <sup>[1]</sup>
	Inhalation (rat) LC50: 8.5 mg/l/4H <sup>[2]</sup>
	Oral (rat) LD50: >4500 mg/kg <sup>[1]</sup>
<b>2-ethylhexyl nitrate</b>	<b>TOXICITY</b>
	dermal (rat) LD50: >4820 mg/kg <sup>[2]</sup>
	Inhalation (rat) LC50: >1.15 mg/l/1h, <sup>[2]</sup>
	Oral (rat) LD50: >2000 mg/kg <sup>[2]</sup>
<b>solvent naphtha petroleum, heavy aromatic</b>	<b>TOXICITY</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>
	Inhalation (rat) LC50: >0.59 mg/l/4H <sup>[2]</sup>
	Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY</b>	<p>C9-C11 cyclic aliphatics were administered via oral gavage to 5 male and 5 female rats at a dose of 5000 mg/kg to assess acute oral toxicity. Animals were observed daily for 15 days post dosing. At a dose of 5000 mg/kg, signs of toxicity were sedation, dyspnea, hunched posture and ruffled fur. All animals had recovered until day 5 of observation and survived to study termination. C9-C11 cyclic aliphatics were administered via individual inhalation chambers for eight hours to eight Sprague-Dawley rats at vapor concentration of 0 (air), 1 g/m<sup>3</sup> (170ppm), 2.5 g/m<sup>3</sup> (430ppm), 5 g/m<sup>3</sup> (860ppm) for three consecutive days. There was no mortality noted in any of the animals. Based on the conditions of this study, the LC50 for acute inhalation exposure to C9-C11 cyclic aliphatics vapor is greater than the highest obtainable vapor concentration (5 g/m<sup>3</sup>). Classification as an acute inhalation toxicant is not warranted. Five male and five female rabbits were exposed to P-D 20/26 for 24h via an occluded patch. Dermal evaluations occurred at 24 hours post patch removal and twice daily until the study termination at day 14. Exposure had no effect on viability; all animals survived the exposure. The LD50 of P-D 20/26 was &gt; 2000 mg/kg. Skin irritation: Three rabbits were subjected to a 4h dermal (shaved) exposure of 0.5 ml of ECOLANE 90 via a semi-occluded patch. Dermal responses were evaluated at 1, 24, 48, and 72h post-dosing and once a day for a total of 14 days according to the Draize method of scoring. A very slight or well-defined erythema was observed in all animals from day 1 up to day 9 or 10. A slight oedema was noted in two animals on day 1 only. Eye Irritation: C9-C11, cyclic aliphatics was administered to the left eye of three male and three female rabbits to assess for ocular irritation. Ocular examinations occurred at 1h, 24h, 48h, 72h. Ocular damage was assessed and scored according to the Draize eye test. All animals survived the exposure. Sensitisation: A Magnusson and Kligman Guinea-Pig Maximization test was conducted on 20 guinea pigs with Shellsol TD. Twenty guinea pigs were treated by intradermal injection (1.0% (w/v) Shellsol TD in vehicle) to induce sensitization and then further sensitized by dermal application of 50.0% (w/v) Shellsol TD. Guinea Pigs were challenged by topical application (25.0% (w/v) Shellsol TD in corn oil). All animals survived to termination of study. In humans, MRD-88-296 showed no evidence of being a photocontact allergen and no evidence of being either a primary irritant or a contact allergen. Based on these data and results, MRD-88-296 would not be classified as a dermal irritant or as a dermal sensitizer. Repeat dose toxicity: oral Results of subchronic exposure of tetramethylcyclohexane (TMCH) to rats and dogs failed to show any treatment-related morphological or qualitative changes in the cellular elements of the peripheral blood picture. This result is consistent with a similar lack of effects noted after acute TMCH exposure. The NOAEL for rats was 3000ppm. The NOAEL for dogs was 1000ppm. Genetic toxicity: in vitro No Shellsol TD treatments of any of the test strains, either in the absence or in the presence of S-9, resulted in a statistically significant increase in revertant numbers, when the data were analysed at the 1% level using Dunnett's test. This study was therefore considered to have provided no indication of any SHELLSOL TD mutagenic activity. The test to assess the genotoxicity of the test material was negative. This finding does not warrant the classification of this test material as a genotoxin. Genetic toxicity: in vivo MRD-77-43 when administered by vapor inhalation to male rats is not considered mutagenic by the dominant lethal test. This finding does not warrant the classification of MRD-77-43 as a genotoxin. Toxicity to Reproduction: The NOAEL &gt;=3000 mg/kg/day for male rat fertility. Male rats were given 0, 750, 1500 or 3000 mg/kg neat JP-8 daily by gavage for 70 days prior to mating with naive females to assess fertility and sperm parameters. Males were allowed to mate while continuing to receive treatment. Aside from a decrement in male body weight, no clinical signs were observed. There were no statistical differences noted in any reproductive parameter measured. Developmental toxicity: No adverse effects due to exposure to the test substance were seen in either dams or fetuses. No treatment related malformation effects were noted in the fetuses. The developmental NOAEC for rats by inhalation is &gt;=300 ppm. The test substance is also not teratogeni * REACh Dossier</p> <p>The safety of isoparaffins as used in cosmetic products was reviewed by the Cosmetic Ingredient Review (CIR) Expert Panel. These ingredients function mostly as solvents and also function as emollients in the 0001% to 90% concentration range. The CIR Expert Panel has reviewed relevant animal and clinical data and concluded that these ingredients are safe in the present practices of use and concentration. The CIR Expert Panel noted that most of the available data related to oral or inhalation exposure to isoparaffins, but the dermal and ocular exposure data that were available, suggested mild ocular irritation, mild-to-severe irritation, no sensitization or photosensitization, and no phototoxicity. No significant toxicity was identified in oral or inhalation exposure studies of the following end points: genotoxicity, reproductive and developmental toxicity, or carcinogenicity. Nephrotoxicity, however, was a concern. The Expert Panel noted the involvement of a2u-globulin in the mechanism for isoparaffin-induced nephrotoxicity/renal tubule cell proliferation in male rats of various strains in oral and inhalation exposure studies.</p>
<b>2-ETHYLHEXYL NITRATE</b>	Chemical with the aliphatic nitro group (-C-NO <sub>2</sub> ) have been added to a list of DNA-reactive subgroups recognised by the National Toxicological Program (NTP, U.S. Dept Health and Human Services) for possible carcinogenic activity.

<b>SOLVENT NAPHTHA PETROLEUM, HEAVY AROMATIC</b>	For petroleum: This product contains benzene, which can cause acute myeloid leukaemia, and n-hexane, which can be metabolized to compounds which are toxic to the nervous system. This product contains toluene, and animal studies suggest high concentrations of toluene lead to hearing loss. This product contains ethyl benzene and naphthalene, from which animal testing shows evidence of tumour formation. Cancer-causing potential: Animal testing shows inhaling petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans. Mutation-causing potential: Most studies involving gasoline have returned negative results regarding the potential to cause mutations, including all recent studies in living human subjects (such as in petrol service station attendants).		
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY &amp; SOLVENT NAPHTHA PETROLEUM, HEAVY AROMATIC</b>	Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins. The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell.		
<b>Acute Toxicity</b>	✗	<b>Carcinogenicity</b>	✗
<b>Skin Irritation/Corrosion</b>	✗	<b>Reproductivity</b>	✗
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✗
<b>Respiratory or Skin sensitisation</b>	✗	<b>STOT - Repeated Exposure</b>	✗
<b>Mutagenicity</b>	✗	<b>Aspiration Hazard</b>	✓

Legend: ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

### Toxicity

2005 DIESEL PURGE, 500ml	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
Naphtha (petroleum), hydrotreated heavy	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	48	Crustacea	>1-mg/L	2
	EL0	48	Crustacea	1-mg/L	2
2-ethylhexyl nitrate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	2mg/L	2
	EC50	48	Crustacea	>12.6mg/L	2
	EC50	72	Algae or other aquatic plants	1.57mg/L	2
	EC10	72	Algae or other aquatic plants	0.76mg/L	2
	NOEC	96	Fish	1.52mg/L	2
solvent naphtha petroleum, heavy aromatic	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.58mg/L	2
	EC50	48	Crustacea	0.76mg/L	2
	EC50	72	Algae or other aquatic plants	<1mg/L	1
	NOEC	96	Algae or other aquatic plants	0.12mg/L	2

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

**DO NOT discharge into sewer or waterways.**

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

### Bioaccumulative potential

Ingredient	Bioaccumulation
solvent naphtha petroleum, heavy aromatic	LOW (BCF = 159)

### Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

2005 DIESEL PURGE, 500ml


**SECTION 13 DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Authority for disposal.</li> <li>▶ Bury or incinerate residue at an approved site.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
-------------------------------------	---

**SECTION 14 TRANSPORT INFORMATION**

**Labels Required**

<b>Marine Pollutant</b>	
-------------------------	---

**Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION**

**Safety, health and environmental regulations / legislation specific for the substance or mixture**

**NAPHTHA (PETROLEUM), HYDROTREATED HEAVY IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Chemical Footprint Project - Chemicals of High Concern List	US NIOSH Recommended Exposure Limits (RELs)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US ACGIH Threshold Limit Values (TLV)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US AIHA Workplace Environmental Exposure Levels (WEELs)	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US DOE Temporary Emergency Exposure Limits (TEELs)	

**2-ETHYLHEXYL NITRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS**

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory	US TSCA Chemical Substance Inventory - Interim List of Active Substances
---	--

**SOLVENT NAPHTHA PETROLEUM, HEAVY AROMATIC IS FOUND ON THE FOLLOWING REGULATORY LISTS**

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory	US TSCA Chemical Substance Inventory - Interim List of Active Substances
---	--

**Federal Regulations**

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**SECTION 311/312 HAZARD CATEGORIES**

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No



Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	Yes
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

**US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)**

None Reported

**State Regulations****US. CALIFORNIA PROPOSITION 65**

None Reported

**National Inventory Status**

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (Naphtha (petroleum), hydrotreated heavy; 2-ethylhexyl nitrate; solvent naphtha petroleum, heavy aromatic)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (Naphtha (petroleum), hydrotreated heavy; solvent naphtha petroleum, heavy aromatic)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (2-ethylhexyl nitrate)
Vietnam - NCI	Yes
Russia - ARIPS	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

**SECTION 16 OTHER INFORMATION**

<b>Revision Date</b>	01/11/2019
<b>Initial Date</b>	26/03/2018

**SDS Version Summary**

Version	Issue Date	Sections Updated
3.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC—TWA: Permissible Concentration-Time Weighted Average  
 PC—STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.