

Top Tec Gear EV 520

Description

The latest generation of low-viscosity high-performance transmission fluid based on synthetic technology. With modern, powerful additive components. Ensures outstanding aging and oxidation stability under all operating conditions. Has a very high viscosity index and enables long oil-change intervals.



Properties

- excellent viscosity/temperature properties
- prevents foam formation
- high resistance to aging
- very good low-temperature properties
- excellent corrosion protection
- high wear resistance
- outstanding resistance to oxidation

Available pack sizes

1 l Can plastic	21755
	D-GB-I-E-P
20 l Canister plastic	21756
	D-GB-I-E-P

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Cadillac • Ford • Mazda

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Density at 15 °C	0,840 g/cm ³ DIN 51757
Viscosity at 40 °C	19,3 mm ² /s ASTM D7042
Viscosity at 100 °C	4,5 mm ² /s ASTM D7042
Viscosity at -40 °C (Brookfield)	≤ 10000 mPas ASTM D2983
Viscosity index	150 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color / appearance	red

Areas of application

A lubricant of this quality is required in the electric differential of various Ford and Cadillac vehicles.

Application

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes