

Top Tec ATF 1800

Description

The latest generation of low-viscosity high-performance automatic transmission fluid based on synthetic technology. With modern, powerful additive components. Guarantees outstanding aging and oxidation stability as well as ideal shifting under all operating conditions thanks to its extremely high viscosity index. Makes long oil change intervals possible.

Properties

- high wear resistance
- excellent corrosion protection
- excellent viscosity/temperature properties
- high resistance to aging
- outstanding resistance to oxidation
- outstanding friction characteristics
- very good low-temperature properties
- prevents foam formation
- enables a multifaceted range of applications

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Aisin Warner AW-1 • BMW 83 22 0 142 516 • BMW 83 22 2 152 426 • BMW 83 22 2 289 720 • BMW 83 22 2 305 396 • BMW 83 22 2 305 397 • BMW 83 22 2 355 599 • BMW M-1375.4 • Dexron VI • Fiat 9.55550-AV5 • Ford Mercon LV • Honda ATF 3.1 • Honda ATF DW-1 • Honda Typ 3.0 • Hyundai SP-IV • Hyundai SP-IV-RR • Isuzu ATF WSI • JASO 1A-LV • JWS 3324 (Aisin Warner) • Land Rover TYK 500050 • Mazda ATF FZ • MB 236.12 • MB 236.14 • Mitsubishi Dia Queen ATF-MA1 • Mitsubishi Dia Queen ATF-PA • Nissan AT-Matic S Fluid • Nissan Matic P • Toyota WS • VW G 055 005 • VW G 055 162 • VW G 055 540 • VW G 060 162

Technical data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	28,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	5,8 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	≤ 15000 mPas ASTM D 2983-09
Viscosity index	155 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color / appearance	bräunlich/brownish



Technical data

Color number (ASTM)	4
	DIN ISO 2049

Areas of application

Primarily developed for automatic transmissions of various manufacturers such as Aisin Warner, ZF, etc., which are installed in various vehicles of Audi, BMW, Ford, Honda, Hyundai, Jeep, Jaguar, Kia, Land Rover, Lexus, Mazda, Mercedes-Benz, Mini, Opel, Peugeot, Porsche, Toyota, VW, Volvo, etc. Meets further manufacturer specifications, allowing it to cover an even wider range of vehicles.

Application

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Can plastic	3687 DE-EN-ES-IT-PT
1 l Can plastic	9704 AR-DE-EN-FR
1 l Can plastic	20461 CS-HU-PL-RO-SK-TR
1 l Can plastic	21107 D-GB-CN
1 l Can plastic	21234 DZAR-EN-FR
5 l Canister plastic	20662 DE-EN-ES-IT-PT
5 l Canister plastic	21256 DZAR-EN-FR
5 l Canister plastic	21686 HU-PL-RO-TR
20 l Canister plastic	3688 DE-EN-ES-IT-PT
60 l Black plate barrel	3689 DE-EN

Top Tec ATF 1800

Available pack sizes

205 l Black plate barrel 20624
DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.