Product information

PI 11/07/20/2026

Motorbike Molygen 4T 5W-30 Scooter

Description

High-performance motor oil. With an innovative recipe and the added bonus of the special Molygen additive. Ensures the best possible protection and retention of engine value as well as perfect lubrication and maximum performance under all operating conditions. Prevents the formation of deposits, lowers frictional losses in the engine and considerably reduces wear. This extends the engine's service life and reduces consumption. Tested on engines with catalytic converters.



Properties

- optimum stability to aging
- tested for the use with catalytic converters
- excellent wear resistance
- optimum lubrication under all operating conditions
- ensures maximum engine performance
- guarantees low oil consumption
- outstanding engine cleanliness

Specifications / Approvals

API SN PLUS

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

JASO MB

Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,850 g/cm³ DIN 51757
Viscosity at 40 °C	64,0 mm²/s ASTM D7042-04
Viscosity at 100 °C	11,0 mm²/s ASTM D7042-04
Viscosity index	165 DIN ISO 2909
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
HTHS at 150°C	⩾ 2,9 mPas ASTM D 5481
Pour point	-36 °C DIN ISO 3016
Flash point	230 °C DIN ISO 2592
Evaporation loss (Noack)	12,0 % ASTM D5800-08 Method B
Total base number	7,0 mg KOH/g DIN ISO 3771

Technical data

Sulfate ash	0,8 g/100g DIN 51575
Color / appearance	green, fluorescent

Areas of application

For air and water-cooled 4-stroke scooter engines with dry clutch, automatic or Variomatic transmission that require a lubricant of this specification. Suitable for normal to extreme operating conditions.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

800 ml Canister plastic	21895 DE-EN
1 l Canister plastic	21718 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com