

Liquimate 8300 Seam Sealant black

Description

High-grade, 1-component, MS polymer-based, sprayable seam sealant. Free of isocyanate and silicone. Resistant to UV and mineral oils. With most commercially available paints, can be painted over wet-on-wet immediately (max. up to 2 hours).

Properties

- waterproof
- free of isocyanate
- can be used without primer
- silicone-free
- permanently elastic after curing
- can be applied as a spray or with a brush
- outstanding rigidity
- broad adhesive spectrum
- odorless
- resistant to mineral oils
- can be painted over wet-in-wet
- high resistance to aging
- Sealing compound and sprayable seam sealant
- easy to use
- professional repairs
- high adhesive strength
- fast-drying

Technical data

Curing rate at 23 °C / 50 % rh	~ 3 mm/24 h DIN 50 015
Skin formation time at 23 °C/50 % relative humidity	20 min DIN 50 015
Color / appearance	black
Elongation at break	250 %
Hardness, Shore A	47 DIN 53 505
Thermal stability after curing	-120 °C
Tensile strength	2,1 N/mm ²
Form	pastelike
Odor	petrol-like
Curing system	cured by moisture in the air
Density at 20 °C	1,38 g/cm ³
Base	MS-Polymer
Tear growth resistance	5 N/mm DIN 53515
Shelf life in original sealed container	18 months
Recommended storage temperature	≤ 25 °C



Areas of application

For sealing seams during repairs to restore to original factory condition. Areas of application include the engine compartment, trunk and wheel housings.

Application

Surfaces must be clean and free of grease. Can be painted over after application of the material with solvent- and water-based paints. It is recommended that you check the adhesion and compatibility with plastics and paints for the specific object.

Available pack sizes

310 ml Cartridge plastic 6151
D-GB-F-I-E-NL-P

Our information is based on thorough research and may be considered reliable, although not legally binding.