Product information
DFI Cleaner

PI 14/11/12/2026



Description

Modern fuel additive with polyetheramine technology. Thanks to the use of active PEA, achieves the greatest cleaning effect in the fuel system as well as excellent piston and combustion chamber cleanliness. Considerably reduces the risk for damage to the engine due to low-speed pre-ignition (LSPI).

Properties

- cleans the fuel system
- polyetheramine technology
- excellent cleaning effect
- cleans the combustion chamber and injectors
- outstanding engine cleanliness

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Opel 95527846 • Opel 95527847 • Opel 95599923

Technical data

Base	Additive mixture in carrier fluid
Color / appearance	light yellow, transparent
Density at 15 °C	0,886 g/cm³
Flash point	74 °C
Odor	n.a.
Form	liquid
Viscosity at 40 °C	12,5 mm²/s

Areas of application

Suitable for all passenger cars with 4-stroke gasoline engines.

Application

120 ml can formulated for 30 – 50 l of fuel. For the ideal effect, add to the fuel every 5,000 km at the earliest. Mixing takes place automatically.

OEM recommendations may differ from the standard dosage. Note manufacturer's instructions!

Available pack sizes

120 ml Can sheet metal	21377 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com