

## Motorbike Gear Oil 80W-90

### Description

Mineral high-pressure gear oil of API GL-4 performance class based on selected base oils and multifunctional additives. For universal use in a number of transmissions and final drives.

### Properties

- high wear resistance
- high pressure-absorption capability
- reduces running noise
- excellent high and low temperature behavior
- high resistance to aging
- does not attack common sealing materials



**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Specifications / Approvals

API GL4

### Technical data

SAE class (gear oils)	80W-90 SAE J306
Density at 15 °C	0,895 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	143 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -26 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	100 DIN ISO 2909
Pour point	-30 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Color number (ASTM)	L3,0 DIN ISO 2049

### Areas of application

For transmissions and final drives operating under normal and high load. Note the transmission manufacturer's instructions.

### Application

Note the transmission manufacturer's instructions. Mixable with all branded gear oils. Optimum effect only when the product is used unmixed.

### Available pack sizes

1 l Can plastic 3821  
D-GB-I-E-P